


MOON!

5302 - LAMP H. 16 IN.

DESIGN BY TRISTAN LOHNER

RESIDENTIAL CONTRACT INTENSIVE



Aluminum frame
 Polyethylene diffuser
 Lighting intensity : 2 warm white (100% & 50%) + 2 cool white (100% & 50%) + OFF
 T° color : 1 warm white (3000°K) and 1 cool white (6000°K)
 Technology LED - 2.5 W
 Luminous flux : 150 lm
 Min. Battery life : 8 h - Max. : 16 h
 Rechargeable (7h)
 Type of power supply : USB - Cable (supplied) 78 in.
 Controlled with switch
 Bypass to prevent battery damage during wired use
 IP44 (ingress protection) | IK10 (impact resistance) | CE | FCC
 Powered by Smart & Green



1,6 lb

- 530282 ● Cactus
- 530273 ● Honey
- 530214 ● Nutmeg

- 530247 ● Anthracite
- 530221 ● Acapulco Blue
- 530220 ● Red Ochre


NEW
NEW
NEW

5320 - LAMP H. 25 IN.

DESIGN BY TRISTAN LOHNER

NEW

RESIDENTIAL CONTRACT INTENSIVE



Aluminum frame
 Polyethylene diffuser
 Lighting intensity : 2 warm white (100% & 50%) + 2 cool white (100% & 50%) + OFF
 T° color : 1 warm white (3000°K) and 1 cool white (6000°K)
 Technology LED - 7 W
 Luminous flux : 500 lm
 Min. Battery life : 7 h - Max. : 13 h
 Rechargeable (4h)
 Type of power supply : ABS plastic charging base & transformer
 I 10-230 Apv*/24 Dpv** IPX0 Multi-type sockets - Cable (supplied) 59 in.
 Touch-activated light or remotely using the integrated Bluetooth system compatible with the «Fermob Lighting» app
 Bypass to prevent battery damage during wired use
 IP44 (ingress protection) | IK10 (impact resistance) | CE | FCC
 Powered by Smart & Green



5,7 lb

- 532082 ● Cactus
- 532047 ● Anthracite


- 532021 ● Acapulco Blue
- 532020 ● Red Ochre

NEW


NEW
NEW

MOON!

5310 - LAMP H.53 IN.
DESIGN BY TRISTAN LOHNER



Aluminum frame
Polyethylene diffuser
Lighting intensity : 2 warm white (100% & 50%) + 2 cool white (100% & 50%) + OFF
T° color : 1 warm white (3000°K) and cool white (6000°K)
Technology LED - 7 W
Luminous flux : 500 lm
Min. Battery life : 7 h - Max. : 13 h
Rechargeable (4h)
Type of power supply : ABS plastic charging base & transformer
I 10-230 Apv*/24 Dpv** IPX0 Multi-type sockets - Cable (supplied) 59 in.
Touch-activated light or remotely using the integrated Bluetooth system compatible with the «Fermob Lighting» app
Bypass to prevent battery damage during wired use
IP44 (ingress protection) | IK10 (impact resistance) | CE | FCC
Powered by Smart & Green



11,9 lb

531082 ● Cactus
531047 ● Anthracite

NEW

531021 ● Acapulco Blue
531020 ● Red Ochre

NEW
NEW



MOON! & BELLEVIE

* Alternating power volt / **Direct power volt