

## TADEO CONFERENCING. Design: EOOS.

---



Tadeo Conferencing brings this naturalness and honest craftsmanship into the office. The sturdy solid wood top rests on the recessed base, in archaic fashion like an altar. Regal and secure, warm and lively, original and sustainable. Every table is unique - if required, equipped with modern media technology for the routines of everyday business.

### Product description

---

#### Modell no.

2960

---

#### Table top

Solid wood with cross-wise grain:

- oak white pigmented, oiled (.10wo).
- oak fumed, oiled (.13wo).
- oak burned, oiled (.14wo).
- nutwood with sapwood inclusions, oiled (.99wo).

Top thickness: 46 mm (including raised edge).

---

#### Base

Table legs in solid wood:

- oak white pigmented, oiled (.10wo).
- oak fumed, oiled (.13wo).
- oak burned, oiled (.14wo).
- nutwood with sapwood inclusions, oiled (.99wo).

Panel legs: aluminium powder-coated bronze matt or powder-coated black matt.

---

#### Glides

Table legs and panel legs fitted with synthetic glides.

---

#### Plug management

All tables are fitted with a horizontal cable duct. This runs along the interior sides of the two longitudinal frames. Cable ducts and frames are available in a matt black powder-coated finish.

A vertical cable duct is available as an option and can be attached to predefined positions below the table top.

All Tadeo Conferencing tables can be fitted with connectors for electricity and data and video equipment. Exterior of connector covered in Congress PG 55 leather.

The connectors are listed in the last part of the price list.

---

#### Notice

*Please note that the colour of solid wood will fade if placed in direct sunlight.*

## TADEO CONFERENCING.

---

### Technical drawings and dimensions

---


Tische mit 4 Füßen/Tables with 4 legs  
Höhe/Height 74

2967




B/W 240 T/D 125

2968



B/W 320 T/D 125


2969



B/W 400 T/D 125


Tische mit Wangen/Tables with panel legs  
Höhe/Height 75

2977




B/W 240 T/D 125

2978



B/W 320 T/D 125

2979



B/W 400 T/D 125

All dimensions in cm.